



Patio Doors

PremiLine & PremiLine PRO KÖMMERLING®

The PremiLine sliding patio door is packed with technical features and compatible with all 70mm systems. Upgrade to PRO for one of the first PAS 24 certified UPVC patio door systems to meet the Lifetime Homes standard.

Features:

- Can offer 2,3 or even 4 panel openings.
- High quality stainless steel tracks for maximum possible service life and smooth running.
- Aluminium reinforced for security, stability and to achieve large units.
- Low sightline gaskets in black or grey.
- Low threshold & full length handle also available.



PremiDoor 76 KÖMMERLING® Lift & Slide

Capable of incredible opening sizes, up to 6.5m wide, two pane and 2.9m high. It offers outstanding thermal, acoustic and weather properties. The thermally broken frame provides energy efficiency and structural integrity.

Features:

- High stability for floor to ceiling elements up to 2.90m.
- Excellent heat transfer coefficient $U_f = 1.2-1.3 \text{ W}/(\text{m}^2\text{K})$, an optional UD value of max $0.8 \text{ W}/(\text{m}^2\text{K})$ is possible.
- High insulation WPC threshold.
- Reliable functionality, great handling ease, easy to open and close as if sliding on air.
- Three sealing levels ensure the optimal protection against wind, rain, and outside noise.
- Ease of handling with smooth gliding operation.